



**ARDON**<sup>®</sup>  
**WORKWEAR**  
**& OUTDOOR**

## ARDON<sup>®</sup> LEADER S3

SAFETY SHOES



TECHNICAL SHEET



**DEFUSE  
CONTROL**




**DRY AIR**



**WATER  
REPELLENT**



**REFLECTIVE**



**NONMETALLIC**



**ARDON**<sup>®</sup>  
**WORKWEAR**  
 & **OUTDOOR**

# ARDON<sup>®</sup> LEADER S3

SAFETY SHOES

**ARTICLE** G3392

**MATERIAL**

Upper NUBUCK cowhide leather, thickness 1.8 - 2 mm, hydrophobic /fabric  
 Lining MESH-type laminated breathable fabric  
 Sole PU/PU, direct injection  
 Toe cap Fibreglass 459  
 Plate Kevlar  
 Insole ANATOMIC FOAM – anatomically shaped from EVA foam

**SIZE** 38-48

**UNIT** pair

**PACKAGE**

Units in a carton 10 pairs  
 Units in a box 1 pair

**DIMENSIONS**

	38-42	43-48	
Carton H x W x D (cm)	34 x 48 x 65	37 x 50 x 69	
Carton (cbm)	0,106	0,128	



TECHNICAL SHEET

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	-	-	252	259	266	272	278	286	291	298	306	312	319	-	-	-
Foot length cm	-	-	-	24,2	24,9	25,6	26,2	26,8	27,6	28,1	28,8	29,6	30,2	30,9	-	-	-

**DESCRIPTION**

Safety shoes with an upper made of high-quality NUBUCK leather, hydrophobic and fabric, with a fiberglass toe cap and Kevlar insole, reflective strip for higher visibility, dual-density polyurethane sole.



**ARDON**<sup>®</sup>  
**WORKWEAR**  
 & **OUTDOOR**

## NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment - Safety footwear

Category: S3 CI SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C		
insulation of the bottom of the shoe against heat		
insulation of the bottom of the shoe against the cold	✓	
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts	✓	
-		
-		
-		

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

<b>CODE</b>	<b>EAN</b>	<b>CARTON WEIGHT (KG)</b>	<b>UNIT WEIGHT (KG)</b>
G3392/38	8592390168368	15,0	1,500
G3392/39	8592390168375	15,5	1,550
G3392/40	8592390168382	17,0	1,700
G3392/41	8592390168399	17,3	1,730
G3392/42	8592390168405	18,0	1,800
G3392/43	8592390168412	18,5	1,850
G3392/44	8592390168429	18,8	1,880
G3392/45	8592390168436	19,0	1,900
G3392/46	8592390168443	20,5	2,050
G3392/47	8592390168450	21,0	2,100
G3392/48	8592390168467	22,0	2,200







**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**





**ARDON®**

**WORKWEAR  
& OUTDOOR**



TECHNICAL SHEET